

### What Is Claimed Is:

- 5 1. An implantable medical device comprising:  
a parameter storage unit that is operative to store parameter  
data corresponding to at least two operating configurations;  
a receiver that is operative to receive communication signals  
from an external device; and  
10 a controller that is connected to the parameter storage unit  
and to the receiver and that controls the operation of the  
implantable medical device according to a selected one of the  
operating configurations, wherein the controller is responsive to  
receipt of a reset signal by the receiver to retrieve parameter data  
15 from the parameter storage unit corresponding to another of the  
operating configurations and to implement the parameter data to  
change the operating configuration.
- 20 2. The device of claim 1, wherein the parameter storage unit  
comprises a current state pointer for identifying a current operating  
configuration.
- 25 3. The device of claim 1, wherein the operating configurations  
in the parameter storage unit are ordered such that one of the stored  
operating configurations is selected according to its order in the  
parameter storage unit as the current operating configuration.
4. The device of claim 1, wherein the receiver is configured to  
communicate with an external programmer.

5. A method for controlling operation of an implantable medical device, the method comprising:

maintaining at least two sets of parameters representative of at least two programming states comprising a current programming state and at least one other programming state;

receiving a reset signal for resetting the programming state of the implantable device;

retrieving the corresponding set of parameters based on the received reset signal; and

implementing the retrieved set of parameters to alter the operation of the implantable device.

6. The method of claim 5, wherein receiving a reset signal comprises receiving a reset signal from an external programmer.

7. The method of claim 5, wherein receiving a reset signal comprises receiving a reset signal corresponding to one of the programming states.

8. The method of claim 5, wherein implementing the retrieved set of parameters comprises programming functional components of the implantable device in accordance with the parameters of the selected programming state.

5

10

15

20

Sub  
A2

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

9. An implantable medical device comprising:  
means for storing a plurality of sets of parameter data  
corresponding to respective operating configurations;  
means for receiving communication signals from an external  
device;  
means for controlling the implantable medical device  
according to a selected one of the operating configurations by  
implementing a corresponding set of parameter data; and  
means for changing operating configurations by  
implementing a new set of parameter data in response to receipt of  
a reset signal from the external device.

10

add  
a2

add  
B1